

Introducing the newly re-designed SmartCode[™] keypad electronic deadbolt. This new keyless entry deadbolt is faster and quieter than previous models, while allowing you to enter your home using a personal code—the motorized deadbolt locks with just the push of a button.

The SmartCode[™] keypad is Weiser's first electronic lock to have Microban[®] Antimicrobial Technology on both the finish and keypad protecting you 24/7. Featured in both a traditional and contemporary design that will complement any home decor.

Features

- New 10-button keypad design
- Protected with Microban* Antimicrobial Technology, built into the keypad and finish on select finishes*
- New fast and quiet motorized deadbolt

User Codes

- Up to 50 user access codes for family & guests
- Optional Programming Code for improved access code management


*Not available on Satin Chrome finish




Specifications

_					
Battery	Uses 4 x AA 6V alkaline cell batteries with approximately 1 year battery life				
Function	Single cylinder deadbolt				
Door Prep	1½" (38mm) or 2½" (54mm) diameter cross bore hole and 1" diameter edge bore hole				
Backset	Adjustable 2 ¾" (60mm) or 2 ¾" (70mm)				
Door Thickness	1 ½" (35mm) to 1 ½" (44mm) standard. Thick door service part available for 2-1/4" (57mm) thick doors.				
Faceplates	1" (25 mm) x 2 ¼" (57 mm) square corner faceplate with drive-in collar standard				
Strikes	2 ³ / ₄ " (70mm) x 1 ½" (29mm) square corner 4 hole strike				
Bolt	1" (25mm) throw, steel bolt with anti-saw security pin				
Door Handing	Reversible				
Cylinder	SmartKey Security™				
Temperature Range	Exterior: -40°F to 150°F (-40°C to 66°C) Interior: 32°F to 130°F (0°C to 54°C)				
Humidity	Exterior: 100% condensing Interior: 30% to 95% non-condensing				
Codes	des Up to 50 user codes and 10 one-time user codes with optional programming code				


Dimensions






Traditional

Design	А	В	С	D
Interior	2 ³ /4" (69 mm)	5 ½" (140 mm)	1 ½ " (29 mm)	1 "/16" (43.2 mm)
Exterior	2 ¹³ /16" (71.7 mm)	5" (127 mm)	1" (25 mm)	





Contemporary

Design	A	В	С	D
Interior	2 ³ /4" (69 mm)	5 ½" (140 mm)	1 ½ " (29 mm)	1 "/16" (43.2 mm)
Exterior	2 ³ / ₄ " (71 mm)	4 ⁹ /16 " (116 mm)	1" (25 mm)	

Easy Installation

- Replace existing door hardware with just a Phillips screwdriver
- No hard wiring needed and fits all standard doors
- Download the free BILL app featuring 3D instructions for quick and easy installation
- Operates on 4 AA batteries that will last for approximately 1 year

Innovative Security

- BHMA Grade 2 certified
- 20 Minute fire rating UL certified
- Featuring SmartKey Security[™]

Finishes



9GED92600-001Satin Nickel **15**TRL 15



9GED92600-002Matte Black **514**TRL 514



9GED92600-003Satin Nickel 15
CNT 15



9GED92600-004Matte Black **514**CNT 514



9GED92600-005 Satin Chrome 26D CNT 26D

