


## BEVERLY Box Pack Specifications



BRIGHT BRONZE /  
SATIN CHROME



SATIN CHROME

### AVAILABLE FUNCTIONS:



Passage





Privacy



Entry



Inactive

B		 20 min.	 3 Hour	Bright Bronze / Satin Chrome	Satin Chrome
Passage	GAC101 B	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Privacy	GAC331 B	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Entry	GAC535 B	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Inactive	GAC12 B	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>




20 min.



3 Hour

## SPECIFICATIONS

<b>Door Prep</b>	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
<b>Backset</b>	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
<b>Door Thickness</b>	1-3/8" - 1-3/4" doors standard. 2- 1/4" doors optional on GAC 101 models only
<b>Cylinder</b>	SmartKey, KW 5-pin or WS 5-pin
<b>Faceplates</b>	1" x 2 1/4" Specify round corner or square corner or drive-in"
<b>Strikes</b>	2-1/4" full lip. Specify round corner or square corner Other options including UL 2 Hole Strike available: UL 2 Hole Strike 1" x 2 1/4"
<b>Bolt</b>	1/2" throw. Nickel plated
<b>Door Handing</b>	Reversible for right or left-handed doors
<b>ANSI/BHMA</b>	A156.2 Grade 3
<b>ADA</b>	N/A
<b>UL</b>	Meets 20 minute with Square, Radius or Drive-In used
<b>ASTM</b>	All Weiser product meets ASTM E 331 water penetration testing



Dimensions	A	B	C
Beverly	2 19/32"	2 7/16"	2"

## WARRANTY:

Weiser™ products provide a "Lifetime Mechanical Warranty" that covers all defects in material and workmanship. For more information, please visit [ca.weiserlock.com/en/warranty/](http://ca.weiserlock.com/en/warranty/).