

ELEMENTS BY WEISER KEYPAD

Specifications



90



SATIN NICKEL



MATTE BLACK



GED9240		15 Satin Nickel	514 Matte Black	
Single Cylinder	GED9240 CNT			
Single Cylinder	GED9240 TRL			



SPECIFICATIONS

Battery6V, 4 x AA alkaline batteries, 12-month batterieslife (batteries not included)							
Door Prep		1 1⁄2" (38mm) or 2 1⁄8" (54mm) diameter cross bore hole and 1" diameter edge bore hole					
Backset		Adjustable 2 3/8" (60mm) or 2 3/4" (70mm)					
Door Thickness	1 3/8" (35mm) to 1 3/4" (44mm) standard. Th door service part available for 2-1/4" (57mm) thick doors.						
Faceplates		1" (25 mm) x 2 1⁄4" (57 mm) Includes square corner and drive-in					
Strikes		2 3⁄4" (70mm) x 1 1⁄8" (29mm) Square corner 2-hole strike					
Bolt	1" (25r	1" (25mm) throw, steel bolt					
Door Handing	Rever	Reversible for right or left-handed doors					
Cylinder	KW1 P&T cylinder						
Security	Deadb	Deadbolt: A156.36 Grade 3 Certified					
Temperature Range		Exterior: -40°F to 150°F (-40°C to 66°C) Interior: 32°F to 130°F (0°C to 54°)					
Humidity		Exterior: 100% condensing Interior: 30% to 95% non-condensing					
Codes	Up to 12 user codes and 2 one-time user codes with optional programming code						
Dimensions	А	в	С	D			
GED9240 Contemporary Interior	2 ²³ / ₃₂ "	5 ¹ ⁄2″	1 ⁵ ⁄32″	1 11/16″			
GED9240 Contemporary Exterior	2 ²⁵ ⁄32″	4 7/32"	1 ¹ ⁄32″		B 		
GED9240 Traditional Interior	2 ²³ / ₃₂ "	5 ¹ ⁄2″	1 ⁵ ⁄32″	1 11/16″	Tra		
GED9240 Traditional Exterior	2 11/16″	4 7⁄16″	1 ¹ ⁄32″		F		

Contemporary











WARRANTY:

Weiser[™] electronic products provide a "Lifetime Mechanical and Finish Warranty" and a one-year limited electronics warranty that covers all defects in material and workmanship. For more information, please visit ca.weiserlock.com/en/warranty/.