

FAIRFAX Box Pack Specifications



SATIN NICKEL



SATIN CHROME

AVAILABLE FUNCTIONS:



Passage



Privacy



Entry




Inactive

FAIRFAX	15 Satin Nickel	26D Satin Chrome
Passage	<input type="checkbox"/>	<input type="checkbox"/>
Privacy	<input type="checkbox"/>	<input type="checkbox"/>
Entry	<input type="checkbox"/>	<input type="checkbox"/>
Entry KW	<input type="checkbox"/>	<input type="checkbox"/>
Inactive	<input type="checkbox"/>	<input type="checkbox"/>



SPECIFICATIONS

Door Prep	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4"
Door Thickness	1-3/8" - 1-3/4" doors standard. 2- 1/4" doors optional on GAC 101 models only
Cylinder	SmartKey, KW 5-Pin
Faceplates	1" x 2 1/4" Includes square corner, radius corner and drive-in
Strikes	2-1/4" full lip. Includes square corner and radius corner
Bolt	1/2" throw. Nickel plated
Door Handing	Reversible for right or left-handed doors
ANSI/BHMA	A156.2 Grade 3
ADA	N/A
ASTM	All Weiser product meets ASTM E 331 water penetration testing



Dimensions	A	B	C
Fairfax	2 13/16"	2 7/16"	2 3/8"

WARRANTY:

Weiser™ products provide a "Lifetime Mechanical Warranty" that covers all defects in material and workmanship. For more information, please visit ca.weiserlock.com/en/warranty/.