

## FAIRFAX Box Pack Specifications



SATIN NICKEL



SATIN CHROME



These finishes are available with Microban anti-microbial coating: 15

### AVAILABLE FUNCTIONS:



Passage




Privacy



Entry




Inactive

F		 20 min.	Satin Nickel	Satin Chrome
Passage	GAC101 F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Privacy	GAC331 F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Entry	GAC535 F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Inactive	GAC12 F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

## SPECIFICATIONS



<b>Door Prep</b>	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
<b>Backset</b>	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
<b>Door Thickness</b>	1-3/8" - 1-3/4" doors standard. 2- 1/4" doors optional on GAC 101 models only
<b>Cylinder</b>	SmartKey, KW 5-pin or WS 5-pin
<b>Faceplates</b>	1" x 2 1/4" Specify round corner or square corner or drive-in"
<b>Strikes</b>	2-1/4" full lip. Specify round corner or square corner Other options including UL 2 Hole Strike available: UL 2 Hole Strike 1" x 2 1/4"
<b>Bolt</b>	1/2" throw. Nickel plated
<b>Door Handing</b>	Reversible for right or left-handed doors
<b>ANSI/BHMA</b>	A156.2 Grade 3
<b>ADA</b>	N/A
<b>UL</b>	Meets 20 minute with Square, Radius or Drive-In used
<b>ASTM</b>	All Weiser product meets ASTM E 331 water penetration testing



Dimensions	A	B	C
Fairfax	2 13/16"	2 7/16"	2 3/8"

## WARRANTY:

Weiser™ products provide a "Lifetime Mechanical Warranty" that covers all defects in material and workmanship. For more information, please visit [ca.weiserlock.com/en/warranty/](http://ca.weiserlock.com/en/warranty/).