

# REGINA

## Box Pack Specifications



SATIN NICKEL



SATIN CHROME

### AVAILABLE FUNCTIONS:



Passage





Privacy



Entry




Inactive

RG		 20 min.	 3 Hour	Satin Nickel	Satin Chrome
Passage	SL1000RG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Privacy	SL3000RG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Entry	SL5000RG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Inactive	SL7000RG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Passage 3HR UL	SL1002RG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Entry 3HR UL	SL5002RG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



## SPECIFICATIONS

<b>Door Prep</b>	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1"x2-1/4"
<b>Backset</b>	Adjustable to 2-3/8" or 2-3/4"
<b>Door Thickness</b>	1-3/8"-1-3/4" doors standard. No thick door option
<b>Cylinder</b>	KW 5 pin
<b>Faceplates</b>	1" x 2-1/4" Specify round corner, square corner or drive-in
<b>Strikes</b>	2-1/4" full lip. Specify round corner or square corner
<b>Bolt</b>	1/2" throw
<b>Door Handing</b>	Non-handed
<b>ANSI/BHMA</b>	A156.5 Grade 3
<b>ADA</b>	N/A
<b>UL</b>	Meets UL 3 hour fire rating for all UL functions ULRef # R7860
<b>ASTM</b>	All Weiser product meets ASTM E 331 water penetration testing



Dimensions	A	B	C
Regina	2 9/16"	2 7/8"	1 3/4"

## WARRANTY:

Safelock by Weiser™ products provide a "Lifetime Mechanical & 5 Year-Limited Finish Warranty" that covers all defects in material and workmanship. For more information, please visit [ca.weiserlock.com/en/warranty/](http://ca.weiserlock.com/en/warranty/).