

SMARTCODE RESIDENTIAL LEVER

Specifications





SATIN NICKEL



MATTE BLACK



GED2700		15 Satin Nickel	514 Matte Black
Single Cylinder	GED2700		



SPECIFICATIONS

Battery	Uses 1 x 9V alkaline cell battery with approximately 3 year battery life				
Function	Keyed entry electronic lever				
Door Prep	Cross Bore 2- 1/8". Edge Bore 1"				
Backset	2 ¾" (60mm) or 2 ¾" (70mm)				
Door Thickness	1¾" (35mm) to 1¾" (44mm)				
Faceplates	1" (25 mm) x 2 ¼" (57 mm) square corner standard				
Strikes	Square corner, 2 ¼" (70mm) full lip				
Bolt	½" (12 mm) throw, dead latch				
Door Handing	Reversible				
Cylinder	SmartKey				
Security	Deadbolt: A156.36 Grade 2 Certified				
UL Rating	20 minute				
Temperature Range	Exterior: -40°F to 150°F (-40°C to 66°C) Interior: 32°F to 130°F (0°C to 54°C)				
Humidity	Exterior: 100% condensing Interior: 30% to 95% non-condensing				
Codes	Up to 30 user codes and 1 one-time user code with optional programming code				



					Interior Exterior
Dimensions	Α	В	С	D	DD
GED2700 Interior	5 ²¹ / ₃₂ "	4 1/8"	2 ²⁷ / ₃₂ "	³¹ / ₃₂ "	
GED2700 Exterior	5 ⁹ ⁄16″	4 ²⁹ ⁄ ₃₂ ″	3 ¹ / ₃₂ "	1"	

WARRANTY:

Weiser[™] electronic products provide a "Lifetime Mechanical and Finish Warranty" and a one-year limited electronics warranty that covers all defects in material and workmanship. For more information, please visit ca.weiserlock.com/en/warranty/.