

TOLUCA

Box Pack Specifications







BRASS



MATTE BLACK

AVAILABLE FUNCTIONS:





Passage

Privacy







Inactive


TOLUCA	3 Brass	15 Satin Nickel	514 Matte Black
Passage			
Privacy			
Entry			
Inactive			



SPECIFICATIONS



Door Prep	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"			
Backset	Adjustable to 2-3/8" or 2-3/4"			
Door Thickness	1-3/8" - 1-3/4" doors standard. 2-1/4" doors optional			
Cylinder	SmartKey			
Faceplates	$1^{\circ} \times 2-1/4^{\circ}$. Includes square corner, radius corner and drive-in			
Strikes	2-1/4" full lip. Includes square corner and radius corner			
Bolt	1/2" throw. Nickel plated			
Door Handing	Specify handing only with inactive levers			
ANSI/BHMA	A156.2 Grade 2			
ADA	Functions GLA 101, GLA 12 satisfies section 4.13.9 ADA Requirement			
ASTM	All Weiser product meets ASTM E 331 water penetration testing			



Dimensions	А	В	с	C (Keyed)
Toluca	2 ⁵∕/″	4 ⁷ / ₃₂ "	2 ³ / ₅₂ "	

WARRANTY:

Weiser[™] products provide a "Lifetime Mechanical Warranty" that covers all defects in material and workmanship. For more information, please visit weiserlock.com/en/warranty.