

WESTLEY

Box Pack Specifications







SATIN NICKEL

POLISHED CHROME



SATIN CHROME

AVAILABLE FUNCTIONS:









Passage

Privacy

Entry

Inactive

WTL		20 min.	UL 3 Hour	Satin Nickel	Polished Chrome	Satin Chrome
Passage	SL1000WTL					
Privacy	SL3000WTL					
Entry	SL5000WTL					
Inactive	SL7000WTL					








SPECIFICATIONS

Door Prep	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1"x2-1/4"				
Backset	Adjustable to 2-3/8" or 2-3/4"				
Door Thickness	1-3/8"-1-3/4" doors standard thickness				
Cylinder	P&T(5 pin).				
Faceplates	1"x2-1/4" Must specify square radius or drive-in				
Strikes	2-1/4"full lip. Specify round corner or square corner				
Bolt	1/2"throw. Nickel plated				
Door Handing	Reversible for right or left-handed doors				
ANSI/BHMA	A156.5 Grade 3				
ADA	N/A				
UL	Meets UL 3 hour fire rating for all UL functions				
ASTM	All Weiser product meets ASTM E 331 water penetration testing				



Dimensions	Α	В	С	C (Keyed)
Westley	2 %6"	4 3/52"	2 5/6"	

WARRANTY:

Safelock by Weiser[™] products provide a "Lifetime Mechanical & 5 Year-Limited Finish Warranty" that covers all defects in material and workmanship. For more information, please visit ca.weiserlock.com/en/warranty/.