WEISER

AVALON

Box Pack Specifications





SATIN NICKEL



These finishes are available with Microban anti-microbial coating: 15

AVAILABLE FUNCTIONS:



| AVL | | 20 min. | UL 3 Hour | Satin Nickel |
|----------|--------------|---------|--------------|-----------------|
| Passage | GLA101 AVL | | | |
| Privacy | GLA331 AVL | | | |
| Entry | GLA535 AVL | | | |
| Inactive | GLA12 AVL LH | | | |
| Inactive | GLA12 AVL RH | | | |

WEISER










SPECIFICATIONS

| Door Prep | Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4" | | | | |
|--|---|--|--|--|--|
| Backset | Adjustable to 2-3/8" or 2-3/4" | | | | |
| Door Thickness | 1-3/8" - 1-3/4" doors standard. 2-1/4" doors optional | | | | |
| Cylinder | SmartKey standard, see specific product for more WS and KW availability | | | | |
| Faceplates | 1" x 2-1/4". Round corner, square corner and drive-in available in box | | | | |
| Strikes | 2-1/4" full lip. Other options available | | | | |
| Bolt | 1/2" throw. Nickel plated | | | | |
| Door Handing | Reversible for right or left-hand doors | | | | |
| ANSI/BHMA | A156.2 Grade 2 | | | | |
| ADA | Functions GLA 101, GLA 12 satisfies section 4.13.9 ADA Requirement | | | | |
| UL | Fire rating, see specific product for availability | | | | |
| ASTM All Weiser product meets ASTM E 331 water penetration testing | | | | | |



| Dimensions | Α | В | С | C (Keyed) |
|------------|--------|--------|------|-----------|
| Avalon | 2 5/6" | 4 1⁄4" | 2 ½" | 2 %" |

WARRANTY:

Weiser[™] products provide a "Lifetime Mechanical Warranty" that covers all defects in material and workmanship. For more information, please visit ca.weiserlock.com/en/warranty/.