

HUNTINGTON

Box Pack Specifications



SATIN NICKEL



SATIN CHROME



These finishes are available with Microban anti-microbial coating: 15

AVAILABLE FUNCTIONS:



Passage





Privacy




Entry



Inactive

HT		 20 min.	 3 Hour	Satin Nickel	Satin Chrome
Passage	GA101 HT	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Privacy	GA331 HT	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Entry	GA535 HT	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Inactive	GA12 HT	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Storeroom	GA581 HT	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

SPECIFICATIONS



Door Prep	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" - 1-3/4" doors standard. 2- 1/4" doors optional on GLA 101 and GLA 535 models only
Cylinder	SmartKey, KW 5-pin or WS 5-pin
Faceplates	1" x 2 1/4" Specify round corner or square corner or drive-in
Strikes	2-1/4" full lip. Specify round corner or square corner Other options including UL 2 Hole Strike available: UL 2 Hole Strike 1" x 2 1/4"
Bolt	1/2" throw. Nickel plated
Door Handing	Reversible for right or left-handed doors
ANSI/BHMA	A156.2 Grade 2
ADA	N/A
UL	*Meets 3 hour fire rating for all UL functions when fronted latches used. Meets 20 minute with Square, Radius or Drive-In used
ASTM	All Weiser product meets ASTM E 331 water penetration testing

Dimensions	A	B	C
Huntington	2 5/8"	2 15/16"	2 1/8"

WARRANTY:

Weiser™ products provide a "Lifetime Mechanical Warranty" that covers all defects in material and workmanship. For more information, please visit ca.weiserlock.com/en/warranty/.