

SMARTCODE KEYPAD Specifications



SATIN NICKEL



MATTE BLACK



	GED9260	15 Satin Nickel	514 Matte Black
Single Cylinder	GED9260 CNT	<input type="checkbox"/>	<input type="checkbox"/>
Single Cylinder	GED9260 TRL	<input type="checkbox"/>	<input type="checkbox"/>

SPECIFICATIONS

Battery	Uses 4 x AA 6V alkaline cell batteries with approximately 1 year battery life
Function	Single cylinder deadbolt
Door Prep	1 1/2" (38mm) or 2 1/8" (54mm) diameter cross bore hole and 1" diameter edge bore hole
Backset	Adjustable 2 3/8" (60mm) or 2 3/4" (70mm)
Door Thickness	1 3/8" (35mm) to 1 3/4" (44mm) standard. Thick door service part available for 2-1/4" (57mm) thick doors.
Faceplates	1" (25 mm) x 2 1/4" (57 mm) square corner faceplate with drive-in collar standard
Strikes	2 3/4" (70mm) x 1 1/8" (29mm) square corner, 4 hole strike
Bolt	1" (25mm) throw, steel bolt with anti-saw security pin
Door Handing	Reversible
Cylinder	SmartKey
Security	Deadbolt: A156.36 Grade 2 Certified
Temperature Range	Exterior: -40°F to 150°F (-40°C to 66°C) Interior: 32°F to 130°F (0°C to 54°C)
Humidity	Exterior: 100% condensing Interior: 30% to 95% non-condensing
UL	20 minute
Codes	Up to 50 user codes and 10 one-time user codes with optional programming code



Dimensions	Contemporary				Traditional	
	A	B	C	D	Exterior	Interior
GED9260 Contemporary Interior	2 3/4"	5 1/2"	1 1/8"	1 11/16"		
GED9260 Contemporary Exterior	2 3/4"	4 9/16"	1"	---		
GED9260 Traditional Interior	2 3/4"	5 1/2"	1 1/8"	1 11/16"		
GED9260 Traditional Exterior	2 13/16"	5"	1"	---		

WARRANTY:

Weiser™ electronic products provide a “Lifetime Mechanical and Finish Warranty” and a one-year limited electronics warranty that covers all defects in material and workmanship. For more information, please visit ca.weiserlock.com/en/warranty/.